

# iCam FHD 1080p 10X (H.264)

PeopleLink iCam FHD 1080p 10X (H.264) delivers instant real time, face-to-face experience through its powerful design that enhances your collaboration experience; it provides great productivity benefifts to transform your business. iCam seamlessly connects with your PC / Laptop over USB, so now conduct your large room meetings more ideally, and capture real time speaker expressions and reactions and to efectively communicate with your dispersed teams, Partners & customers.

### **Product Features**

#### > Full Function USB Interface

Full function USB interface, support audio, support compressed video output.

#### > 1080P Full HD

2.07 million effective pixels high quality HD CMOS sensor, can reach maximum  $1920 \times 1080$  high resolution and achieve quality image.

#### > Ultra-high Frame Rate

The output frame rate up to 30fps in 1080P.

#### > Low-light

High SNR of CMOS sensor combined with 2D and 3D noise reduction algorithm, effectively reduce the noise, even under low illumination conditions, picture can still keep clean and clear.

#### > Remote Control

Using RS232 all the parameters of the camera can be remote controlled by the high-speed communications.



### **Product Features**

#### > H.264 Slice/ H.264 SVC Support

Support Slice and SVC encoding mode, adapts to video conference of advance USB application.

#### > Dual stream

Support two stream output (YUY2, MJPEG, H.264 each of both), reduce the host codec pressure

#### > Dual power supply



# **Product Specifications**

#### **Camera**

**Video System** : 1080P, 720P, 540P, 480P, 360P, 240P etc.

**Sensor** : 1/2.7", CMOS, Effective Pixel: 2.07M

Scanning Mode : Progressive

**Lens** : 10x, f4.7mm ~ 46.3mm, F1.8 ~ F2.8

**Digital Zoom** : 16x

Minimal Illumination : 0.5 Lux @ (F1.8, AGC ON)

**Shutter** : 1/30s ~ 1/10000s

White Balance Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K\_1, 6500K\_2,

6500K\_3, One Push,

**Backlight Compensation**: Support

Digital Noise Reduction : 2D&3D Digital Noise Reduction

Video S/N : ≥55dB

**Horizontal Angle of View** :  $58.5^{\circ} \sim 6.5^{\circ}$ 

**Vertical Angle of View** : 35.1° ~ 3.6°

**Horizontal Rotation Range** : ±170°

**Vertical Rotation Range** :  $-30^{\circ} \sim 90^{\circ}$ 

**Pan Speed Range** :  $2.7^{\circ} \sim 35.7^{\circ}/s$ 

Tilt Speed Range :  $2.7^{\circ} \sim 31.5^{\circ}/s$ 

**H & V Flip** : Support

**Image Freeze** : Support

Number of Preset : 255

Preset Accuracy : 0.1°



## **Product Specifications**

#### **USB Featured**

**Operate System** Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android

Color System / YUV 4:2:2 / H.264 / MIPEG

H.264 AVC: max to 1080P@30fps **Video Format** 

H.264 SVC: max to 1080P@30fps MJPEG: max to 1080P@30fps

**USB Video Communication** 

Protocol

UVC 1.0

**UVC PTZ** Support

**Input/Output Interface** 

**USB** Interface 1xUSB2.0: Type B female jack

1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D **Communication Interface** 

/Pelco-P

**Power Jack** JEITA type (DC IN 12V)/USB B type (DC IN 5V)

**Generic Specification** 

**Input Voltage** : DC 12V

**Current Consumption** 0.5A (Max)

**Operating Temperature** -10°C ~ 40°C (14°F ~ 104°F)

**Storage Temperature** -40°C ~ 60°C (-40°F ~ 140°F)

**Power Consumption** 5W (Max)

**MTBF** >30000h

Size 141.3mm x 153mm x 163.6mm

**Net Weight** 1.153 KG

### **PACKAGING INFORMATION**

PeopleLink iCam HD 1080p 10X (H.264) : PPU-PVC-FHD-H264-10X Ordering Information

#### **GLOBAL HEADQUARTERS**

Q3-A3, 10th Floor, Cyber Towers, Hitech City, Madhapur, Hyderabad - 500 081 (India) Phone: +91 (40) 66903959 / 60 Email: vc@peoplelinkvc.com

#### INTERNATIONAL CONTACT NUMBERS

USA:+1-321-2163070 Africa: +27-10-5001977 UK:+44-20-35190197 Australia: +61-29-0988367 Canada: +1-647-4964195 Middle East: +973-1-6199342









Follow us: (in) (y) (f) (D) (G+) (n) www.peoplelinkvc.com/social-

DISCLAIMER: PeopleLink Unified Communications Pv. Ltd., All rights reserved. All third party trademarks/ products mentioned (Ifany) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 &ISO/IEC 27001:2013 Certified Company.

